

# Xerox<sup>®</sup> WorkCentre<sup>™</sup> 7220/7225 Color Multifunction Printer

The WorkCentre 7220/7225 Colour Multifunction Printer is built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to **www.connectkey.com**.



Device Specifications				
Control Panel Languages	U.S. English, International English, I Danish, Finnish, Turkish, Greek, Russ			razilian Portuguese, Swedish, Norwegian,
Accessories	1			
Optional	Envelope Tray (Replaces Tray 1) Integrated Office Finisher Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Convenience Stapler (requires Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® Walk up Fax (One- or Two-line options, includes LAN Fax) Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit Adobe® PostScript® Kit			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Devi	ice, this is an interface to third p	arty access control devices, such as co	oin machines and card readers.
Electrical Requirements				
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50 / 60 Hz +/- 3%, 15 A			
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50 / 60 Hz +/- 3%, 10 A			
Power Consumption-115V	WorkCentre 7220		WorkCentre 7225	
Running (Average)	402 watts		370 watts	
Standby Mode	111 watts		118 watts	
Low Power Mode	72 watts		66 watts	
Auto Off / Sleep Mode	4.41 watts (Default time to Sleep m	node = 2 minutes)	4.4 watts (Default time to Sl	eep mode = 2 minutes)
Power Consumption-230V	WorkCentre 7220 WorkCentre 7225			
Running (Average)	389 watts	389 watts 441 watts		
Standby Mode	111 watts		126 watts	
Low Power Mode	66 watts 64 watts			
Auto Off / Sleep Mode	4.83 watts (Default time to Sleep m	node = 2 minutes)	4.79 watts (Default time to S	Sleep mode = 2 minutes)
Warm-up (from Off)	As fast as 214 seconds (Dependent on number of services registered)			
Low Power Recovery	4.5 seconds			
Recovery from Sleep	16.1 seconds			
Operating Environment				
Required Temperature Range	50° to 82° F (10° to 28° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating 6.96 LwAd (B), Standby:	4.26 LwAd (B)		
Sound Pressure Levels	Operating: 52 LpAm (dBA), Standby	/: 26.7 LpAm (dBA)		
Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration	23.0 in. / 585 mm	25.2 in. / 640 mm	44.6 in. / 1,132 mm	257 lbs. / 117 kg
With Integrated Office Finisher	23.0 in. / 585 mm	25.2 in. / 640 mm	44.6 in. / 1,132 mm	284 lbs. / 129 kg
With Office Finisher LX (with Booklet Maker)	45.8 in. / 1,164 mm	25.6 in. / 651 mm	44.6 in. / 1,132 mm	319 lbs. / 145 kg
Certifications				
	FCC Class A Compliant (US), ICES C CSA Listed (UL 60950-1, Second Ed GS Mark ENERGY STAR® EPEAT (United States) GOST NOM Blue Angel ECOLOGO® CE Marked Common Criteria (IEEE 2600.2 star Citrix Certified WHQL IPv6 Ready Cerner MEDITECH SAP To view the latest list of certification	ition)	eCertifications.	

Descent Long III and			
Paper Handling			
Duplex Automatic Document Feed			
Capacity <sup>5</sup>	110 sheets		
Speed	up to 55 image per minute black and white and colour (simplex)		
Paper Sizes	5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 lb. bond to 32 lb. bond / 50 gsm to 128 gsm		
Bypass Tray			
Capacity⁵	50 sheets		
Sizes	Custom sizes: 3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm		
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm		
Types	Bond         Card Stock         Card Stock Reloaded         Custom         Envelopes         Glossy Card Stock         Glossy Card Stock Reloaded         Hole punched         Labels         Letterhead         Lightweight         Lightweight Glossy Card Stock         Lightweight Glossy Card Stock Reloaded         Plain         Plain Reloaded         Preprinted         Recycled         Transparencies		
	Transparencies		
Trays 1 and 2 with Stand (WorkCer			
Capacity⁵	Trays 1-2: 520 sheets each		
Sizes	Custom Sizes from 5.5 x 7.2 in. to 11.7 x 17 in. / 140 x 182 mm to 297 x 432 mm		
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm		
Types	Bond         Card Stock         Card Stock Reloaded         Custom         Glossy Card Stock         Glossy Card Stock Reloaded         Heavyweight Card Stock         Heavyweight Gard Stock         Heavyweight Glossy Card Stock         Heavyweight Glossy Card Stock Reloaded         Hole punched         Labels         Letterhead         Lightweight Glossy Card Stock         Lightweight Glossy Card Stock         Lightweight Glossy Card Stock Reloaded         Plain         Plain         Plain Reloaded         Preprinted         Recycled         Transparencies		
Trays 1-4 (WorkCentre 7220T/7225			
Capacity <sup>5</sup>	Trays 1-4: 520 sheets each		
Sizes	Custom Sizes from 5.5 x 7.2 in. to 11.7 x 17 in. / 140 x 182 mm to 297 x 432 mm		
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm		

Types	Bond		
	Card Stock Card Stock Reloaded		
	Custom		
	Glossy Card Stock		
	Glossy Card Stock Reloaded		
	Heavyweight Card Stock Heavyweight Card Stock Reloaded		
	Heavyweight Glossy Card Stock		
	Heavyweight Glossy Card Stock Reloaded		
	Labels Letterhead		
	Lightweight		
	Lightweight Card Stock		
	Lightweight Card Stock Reloaded Lightweight Glossy Card Stock		
	Lightweight Glossy Card Stock Reloaded		
	Plain		
	Plain Reloaded Preprinted		
	Recycled		
	Transparencies		
Envelope Tray (Optional–Replaces	Τταγ 1)		
Capacity⁵	Up to 60 envelopes		
Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5		
	Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm		
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm		
Total Capacity			
Device Total Capacity⁵	7220/7225: 1,090 sheets		
	7220T/7225T: 2,130 sheets		
Finishing			
Output Trays (Standard)			
Stacking Tray⁵	Dual Catch Tray – up to 250 sheets each, Lower tray offsets		
Integrated Office Finisher (Option	al)		
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3		
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm		
Weights	16 lb. bond to 80 lb. cover / 60 to 256 gsm		
Stapling			
Stuping	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)		
Office Finisher LX (Optional)			
Capacity⁵	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)		
Sizes	7.2 x 8.3 in. to 11.7 x 17 in. / 182 x 210 mm to 297 x 432 mm		
Weights			
Multiposition Stapling	16 lb bond to 80 lb cover / 60 to 256 gsm         50 sheets of 24 lb. bond / 90 gsm		
	אין		
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch		
· ·	X (Score/Crease, Saddle-stitch Staple) (Optional)		
Capacity <sup>5</sup>	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)		
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF		
	Ledger – 11 x 17 in. / A3 SEF		
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm		
Score / Crease	1-15 sheets / unstapled		
Convenience Stapler (Optional-Red			
Capacity <sup>5</sup>	50-sheet stapling		
	5,000 staples Requires a separate outlet		

Сору	WorkCentre 7220	WorkCentre 7225	
First-copy-out Time (Letter/A4-size, from Platen to Centre Tray)	As fast as 8.4 seconds colour As fast as 7.1 seconds black and white	As fast as 8.7 seconds colour As fast as 7.2 seconds black and white	
First-copy-out Time (Letter/A4-size, from DADF to Centre Tray)	As fast as 12.5 seconds colour As fast as 10.9 seconds black and white	As fast as 12.9 seconds colour As fast as 11.3 seconds black and white	
Sides (input:output)	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999		
Resolution (max.)	600 x 600 dpi		
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments		
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed	d (Copy, Print, Fax and Scan)	
Copy Features	Annotation and Bates <sup>™</sup> stamping (with colour capability and font size adjustment)         Authentication for Services (i.e. Colour Copy)         Auto Paper Select         Auto Tray Switching         Automatic 2-sided/Duplex         Booklet Creation         Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built)         Collation         Covers (Front only, front and back, back only, printed inside and out: Blank or Printed)         Dividers (blank)         Edge Erase         Features Help (Intuitive text and graphic descriptions)         ID Card Copy         Image Quality Adjustments         Image Shift (with Auto Centre option)         Invert Image (negative or mirror image)         Large Job Interrupt         Multi-up (up to 15 columns by 15 rows)         Sample Set         Save Job Settings         Single Colour         Stapling         Transparencies		
Xerox <sup>®</sup> Copier Assistant <sup>®</sup>	Xerox <sup>®</sup> Copier Assistant <sup>®</sup> Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox <sup>®</sup> Copier Assistant for free, visit www.xerox.com		
Print			
Print Resolution	Up to 2400 x 600 image quality		
Print Features	Application Defaults         Banner Sheet Enable / Disable         Bidirectional Status         Custom Colour Options (Colour By Words)*         Cover Selection         Delay Print (specific time)         User Permissions         Image Options (Toner Saver, Resolution (Standard, Enhanced, High)         Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)         Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size)         Overlays         Paper Selection by Attribute         LAN Fax (requires optional Fax Kit)         Sample Set         Saved Job (colour jobs can be printed as monochrome)         Secure Print with Timed Deletion         Special Pages (exception page programming: covers, inserts, exception pages)         Store and Recall Driver Settings         Sustainability Features (Xerox* Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)		
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF <sup>3</sup> , JPEG, TIFF, PS <sup>3</sup> , XPS, PCL Colour jobs can be printed as monochrome		

Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit)	
Operating Systems (PostScript Kit required)	Mac OS 10.7, 10.8, 10.9         PowerPC AIX 5         Solaris® 9, 10         Solaris SPARC 10         HP-UX® 11v2         IBM® AIX® 5         Linux® Redhat® Fedora® Core 19 x86         Linux® Redhat Enterprise 4 and 5         openSUSE® 13.1 x64         Ubuntu® 13.10 x64         Itanian HP-UX 11i v3         Unix®	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox <sup>®</sup> Global Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox <sup>®</sup> and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
Print Solutions		
Xerox® Mobile Print Cloud (Optionαl)	Xerox <sup>®</sup> Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft <sup>®</sup> Office <sup>®</sup> rendering and more. Print what you need, when, where and how you need it.	
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.	
Unified Address Book for Fax, Inte	rnet Fax, Email and Scan to	
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.	
Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed	Scan at up to 55 ipm colour scanning, up to 55 ipm black and white – 8.5 x 11 in. / A4 LEF	
Resolution	From 72 x 72 dpi up to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)	
Maximum Scan Area	11 x 17 in. / A3	
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options	
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression–single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF / PDF/A	

Document Management Fields (Meta Data)	<ul> <li>Features only available in Network Scan to File Templates:</li> <li>1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations</li> <li>Customised fields viewed on user interface for variable data input</li> </ul>		
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)		
Scan to Email (Standard)			
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options     Scan to Email S/MIME Encryption     Email Signing (requires Smart Card option)     Auto send to self		
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)		
Scan to (Standard)			
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)		
Network Scanning – Software Solu	utions		
Xerox® Scan to PC Desktop® Professional (Optional)	<ul> <li>A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:</li> <li>PaperPort Professional image viewing and file management software <ul> <li>Complete PDF functionality</li> <li>Secure PDF workflow of all scanning applications</li> </ul> </li> <li>OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion</li> <li>Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability</li> </ul>		
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® multifunction printer, you can route documents directly into the precise document repository folder, just like you would from your PC. At the multifunction printer, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.		
Xerox® ConnectKey® Share to Cloud (Optional)	Xerox <sup>®</sup> ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox <sup>®</sup> multifunction printer to popular cloud services and email, such as Google Docs <sup>™</sup> , SalesForce.com, Office 365 and Dropbox <sup>™</sup> and gives employees anytime, anywhere access to their most important documents using mobile devices.		
Xerox® ConnectKey® for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (multifunction printer).		
Security			
Features	<ul> <li>Expanded Authentication <ul> <li>Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP</li> <li>Xerox Secure Access Unified ID System<sup>®</sup></li> <li>Local Authentication (internal database)</li> <li>Smart Card authentication -144k CAC/PIV Card Support (2048 bit certificate key)/.NET</li> </ul> </li> <li>Secure Data <ul> <li>Digitally signed PDF (when using Smart Card authentication)</li> <li>Encrypted Scan to Email</li> <li>Encrypted/Password Protected PDF (when using Email and Network Scan Templates only)</li> <li>Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>Immediate Image Overwrite</li> <li>On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>FIPS 140-2 256 bit Hard Disk Encryption</li> </ul> </li> <li>Expanded Authorisation <ul> <li>Sa cccess based on network credentials</li> <li>Authorisation per user per service</li> <li>User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver</li> <li>Secure Network Access</li> <li>IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPs, 802.1X, Cisco<sup>®</sup> TrustSec Identity Services Engine (ISE) integration, Device Security <ul> <li>McAfee<sup>®</sup> Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional)</li> <li>Common Criteria Certification ISO 15/08</li> </ul> </li> </ul></li></ul>		
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions		

Fax			
Network Server Fax Features			
Compatibility	ITU (CCITT) group 3		
	Various Xerox Alliance Partner Solutions		
Maximum Scan Area	11 x 17 in. / A3		
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)		
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print		
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi		
Internet Fax Features			
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients		
Directory Access	Utilises the Unified Address Book		
Send / Receive	Multi-page TIFF, Image only PDF		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)		
Network Protocols	SMTP (send), POP3 (receive)		
Compliance	ITU-T T.37 compliant		
Walk-up Fax Features (Optional (Cu	ustomer-installable) – 1 and 2 lines)		
Compatibility	ITU (CCITT) Group 3		
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilising T38 (optional)		
Compression / Speed	MH/G3, MMR/SG3		
Resolution	Walkup Send:Standard: 200 x 100 dpiFine: 200 x 200 dpiSuperfine: 600 x 600 dpiReceive:Accepts all sizes		
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)		
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay		
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only		
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report		
Directory Access	Utilises the Unified Address Book Group fax available		
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals		

Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources		
Xerox® CentreWare® Web	<ul> <li>MIB RFC 2790, Printer MIB RFC 1759 v.2</li> <li>A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:</li> <li>Works with any SNMP-managed printer from any manufacturer.</li> <li>Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher.</li> <li>CentreWare Integration available for Tivoli<sup>®</sup> NetView<sup>®</sup>, Unicentre TNG<sup>®</sup>, Microsoft Management Console (MMC), HP<sup>®</sup> OpenView<sup>®</sup></li> </ul>		
Novell NDPS/NEPS	Server gateway application: centralised management tool.		
Xerox® Device Manager	<ul> <li>Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:</li> <li>Device monitoring and troubleshooting</li> <li>Extensive reporting and discovery of new devices</li> <li>Usage collection, chargeback and billing capabilities</li> </ul>		
Xerox <sup>®</sup> Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions		
Xerox <sup>®</sup> Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions		
CentreWare Internet Services – Int	tegrated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS <sup>4</sup> , TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese		
Remote Print Services			
Automatic Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time- consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Automatic Supplies Replacement (ASR)	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).		
Accounting			
Xerox <sup>®</sup> Standard Accounting (Stan	dard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>		
Accounting Options – Network Acc	ounting – Third Party Enablement		
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>		

Supplies			
Toner Cartridges (Sold)	Black	22,000 pages⁵	006R01461
	Cyan	15,000 pages⁴	006R01462
	Magenta	15,000 pages⁴	006R01463
	Yellow	15,000 pages⁵	006R01464
Staple Cartridges	for Integrated Office Finisher, Office Finisher LX and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897
Staple Refills	for Integrated Office Finisher, Office Finisher LX and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941
Xerox® Smart Kit®			
Drum Cartridge	Black	7220: 67,000 pages <sup>7</sup> 7225: 74,500 pages <sup>7</sup>	013R00657
	Cyan	7220: 51,000 pages <sup>7</sup> 7225: 54,500 pages <sup>7</sup>	013R00660
	Magenta	7220: 51,000 pages <sup>7</sup> 7225: 54,500 pages <sup>7</sup>	013R00659
	Yellow	7220: 51,000 pages <sup>7</sup> 7225: 54,500 pages <sup>7</sup>	013R00658
Waste Toner Container	1 Cartridge	33,000 pages <sup>8</sup>	008R13089
Fuser Module	110 Volt 220 Volt	100,000 pages 100,000 pages	008R13087 008R13088
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13086
Transfer Belt	1 Assembly	200,000 pages	001R00610

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> PostScript option is required to print PDFs or PostScript files from a thumb drive.

<sup>4</sup> Only available in the optional Adobe® PostScript® 3™ driver.

<sup>5</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality setpoints.

<sup>7</sup> Average drum yield is based on a run length of 5 pages of 8.5 x 11 in. / A4 LEF pages, with split of 30% colour / 70% black and white pages.

 $^{\rm 8}$  Waste Toner Container yield will vary depending on type of image, area coverage  $\,\%\,$  and Job run length.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office.



