

# Xerox® WorkCentre™ 7830/7835/ 7845/7855 Colour Multifunction Printer

The WorkCentre 7800 Series Colour Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



|   |  |  |  | ~                            |  |
|---|--|--|--|------------------------------|--|
| System Specifications                                   | WorkCentre 7830  | WorkCentre 7835                          | WorkCentre 7845                        | WorkCentre 7855              |  |
| <b>Speed</b><br>Colour / Black and White                | Up to 30 / 30 ppm  | Up to 35 / 35 ppm                        | Up to 45 / 45 ppm                      | Up to 50 / 55 ppm            |  |
| Monthly Duty Cycle <sup>1</sup>                         | Up to 90,000 pages   | Up to 110,000 pages                      | Up to 200,000 pages                    | Up to 300,000 pages          |  |
| Recommended Average Monthly<br>Print Volume²            | 8,000 to 12,000 pages  | 10,000 to 15,000 pages                   | 16,000 to 20,000 pages                 | 18,000 to 22,000 pages       |  |
| Hard Drive / Processor / Memory                         | Minimum 250 GB HDD / 1.2 GHz Du  | ial-core / 2 GB system plus 1 GB page    | memory                                 |                              |  |
| Connectivity  | 10/100/1000Base-T Ethernet, High-S   | peed USB 2.0 Direct Print, Optional Wi-f | Fi (with Xerox® USB Wireless Adapter)  |                              |  |
| Controller Features                                     | Unified Address Book, Remote Cont  | rol Panel, Online Support (accessed fr   | rom the user interface and print drive | r), Configuration Cloning    |  |
| Optional Controller                                     | EFI Server   |  |  |                              |  |
| Copy and Print  |  |  |  |                              |  |
| Copy and Print Resolution                               | Copy: Up to 600 x 600 dpi; Print: Up   | to 1200 x 2400 dpi                       |  |                              |  |
| <b>First-print-out Time</b><br>Colour / Black and White | As fast as 9 / 7.7 seconds   |  | As fast as 7.5 / 6.4 seconds           | As fast as 7.1 / 5.9 seconds |  |
| Page Description Languages                              | Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)   |  |  |                              |  |
| Print Features  | Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Colour By Words   |  |  |                              |  |
| Mobile Printing   | Apple® AirPrint, Xerox® PrintBack, Xerox® Mobile Print Solution (Optional), Xerox® Mobile Print Cloud (Optional), Mopria™ certified, Xerox® Print Service Plug-in for Android™   |  |  |                              |  |
| Scan  |  |  |  |                              |  |
| Standard Features                                       | <b>Destinations:</b> Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; <b>File Formats:</b> PDF, PDF/A, XPS, JPEG, TIFF; <b>Convenience Features:</b> Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A  |  |  |                              |  |
| Optional Features                                       | Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Alliance Partners  |  |  |                              |  |
| Fax   |  |  |  |                              |  |
| Standard Features                                       | Internet Fax, Fax Build Job, Network Server Fax Enablement   |  |  |                              |  |
| Optional Features                                       | Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)   |  |  |                              |  |
| Security  |  |  |  |                              |  |
| Standard Features                                       | McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions |  |  |                              |  |
| Optional Features                                       | McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)   |  |  |                              |  |
| Accounting  |  |  |  |                              |  |
| Standard Features                                       | Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement  |  |  |                              |  |
| Optional Features                                       | Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Alliance Partners   |  |  |                              |  |
|   |  |  |  |                              |  |

| Device Specifications                                  |  |   |  |                                     |  |
|--|--|---|--|-------------------------------------|--|
| Control Panel Languages                                | US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan  |   |  |                                     |  |
| Accessories  |  |   |  |                                     |  |
| Optional   | High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Integrated Office Finisher (optional with 7830/7835 only) Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Professional Finisher Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® EFI Fiery® Network Controller Walk up Fax (One- or Two-line options, includes LAN Fax) Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit |   |  |                                     |  |
| Foreign Device Interface (FDI)<br>(Optional)           | Also known as Auxiliary Access Devi  | ce, this is an interface to third party (   | access control devices, such as coin mad | chines and card readers.            |  |
| Electrical Requirements                                |  |   |  |                                     |  |
| North America  | Voltage: 110-127 VAC +/- 10%<br>Frequency: 50/60 Hz +/- 3%, 15 A   |   |  |                                     |  |
| Europe   | Voltage: 220-240 VAC +/- 10%<br>Frequency: 50/60 Hz +/- 3%, 10 A   |   |  |                                     |  |
| Power Consumption                                      | WorkCentre 7830  | WorkCentre 7835   | WorkCentre 7845                          | WorkCentre 7855                     |  |
| Running (Average)                                      | 110V: 641 watts<br>220V: 643 watts   | 110V: 673 watts<br>220V: 691 watts  | 110V: 750 watts<br>220V: 764 watts       | 110V: 828 watts<br>220V: 862 watts  |  |
| Standby Mode   | 110V and 220V: 62 watts  |   | 110V: 98.6 watts<br>220V: 95.9 watts     | 110V: 85.7 watts<br>220V: 121 watts |  |
| Low Power Mode   | 110V and 220V: 59 watts  | 110V and 220V: 59 watts 110V and 220V: 80.5 watts 110V: 80 watts 220V: 94.6 watts |  |                                     |  |
| Auto Off / Sleep mode                                  | 110V: 4.2 watts 220V: 4.8 watts (Default time to Sleep mode = 2 mins)  110V: 4.3 watts (Default time to Sleep mode = 2 mins)   |   |  | ins)                                |  |
| Warm-up (from Off)                                     | As fast as 194 seconds (Dependent  | As fast as 194 seconds (Dependent on number of services registered)               |  |                                     |  |
| Low Power Recovery                                     | < 9 seconds  |   |  |                                     |  |
| Operating Environment                                  |  |   |  |                                     |  |
| Required Temperature Range                             | 50° to 82° F (10° to 28° C)  |   |  |                                     |  |
| Required Relative Humidity                             | 15% to 85%   |   |  |                                     |  |
| Sound Power Levels<br>Operating<br>Standby             | 6.5 LwAd (B)<br>3.5 LwAd (B)   | 6.5 LwAd (B)<br>3.4 LwAd (B)  | 6.6 LwAd (B)<br>3.6 LwAd (B)             | 6.8 LwAd (B)<br>3.6 LwAd (B)        |  |
| <b>Sound Pressure Levels</b><br>Operating<br>Standby   | 54 LpAd (dBA)<br>16.5 LpAd (dBA)   | 54.3 LpAd (dBA)<br>16.5 LpAd (dBA)  | 55.7 LpAd (dBA)<br>18.5 LpAd (dBA)       | 55.8 LpAd (dBA)<br>18.5 LpAd (dBA)  |  |
| Dimensions and Weight                                  | Width  | Depth   | Height                                   | Weight                              |  |
| Base Configuration                                     | 25.2 in. / 640 mm  | 27.5 in. / 699 mm   | 45.2 in. / 1,149.2 mm                    | 334.2 lbs. / 151.9 kg               |  |
| With Integrated Office Finisher<br>(7830/7835 only)    | 44.4 in. / 1,129 mm  | 27.5 in. / 699 mm   | 45.2 in. / 1,149 mm                      | 348 lbs. / 158 kg                   |  |
| With Office Finisher LX (with<br>Booklet Maker)        | 65.6 in. / 1,666 mm  | 27.9 in. / 709 mm   | 45.2 in. / 1,149 mm                      | 403 lbs. / 183 kg                   |  |
| With Professional Finisher                             | 75.7 in. / 1,922 mm  | 27.5 in. / 699 mm   | 45.2 in. / 1,149 mm                      | 526 lbs. / 239 kg                   |  |
| With Professional Finisher and<br>High Capacity Feeder | 75.7 in. / 1,922 mm  | 27.5 in. / 699 mm   | 45.2 in. / 1,149 mm                      | 590 lbs. / 268 kg                   |  |

| Cartification  |  |   |                 |  |  |
|--|--|---|-----------------|--|--|
| Certifications Too St. A. G. a. D. A. W. D. Y. S. S. S. D. A. G. a. D. A. G. C. D. A. G. D. A. G. C. D. A. G. D. A. G. C. D. A. G. D. G. D. A. G |  |   |                 |  |  |
|  | FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) GS Mark ENERGY STAR® 2.0 EPEAT (United States) GOST NOM Blue Angel ECOLOGO® CE Mark Common Criteria (IEEE 2600.2 standard) Citrix® Certified WHQL IPv6 Ready Cerner MEDITECH SAP To view the latest list of certifications, go to www.xerox.com/OfficeCertii  | fications.  |                 |  |  |
| Paper Handling   | WorkCentre 7830 WorkCentre 7835  | WorkCentre 7845   | WorkCentre 7855 |  |  |
| Duplex Automatic Document Feed   | er   |   |                 |  |  |
| Capacity <sup>3</sup>  | 110 sheets   | 130 sheets (Single-pass DADF)   |                 |  |  |
| Speed  | up to 70 image per minute black and white and colour (simplex)   | up to 80 images per minute black a<br>up to 133 images per minute black a | · ·             |  |  |
| Paper Sizes Sensed   | 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3  |   |                 |  |  |
| Weights  | 16 lb. bond to 32 lb. bond / 60 to 128 gsm   |   |                 |  |  |
| Bypass Tray  |  |   |                 |  |  |
| Capacity <sup>3</sup>  | 100 sheets   |   |                 |  |  |
| Sizes  | Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in. / 89 x 98 mm to 320 x 483 mm  |   |                 |  |  |
| Weights  | 16 lb. bond to 110 lb. cover / 60 to 300 gsm   |   |                 |  |  |
| Types  | Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Lightweight Card Stock Reloaded Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain Reloaded Preprinted Recycled Transparencies |   |                 |  |  |
| 3 Tray Module (Total 2,180 sheets)   | (Optional with WorkCentre 7830/7835 only)  |   |                 |  |  |
| Capacity <sup>3</sup>  | Trays 1-4: 520 sheets each   |   |                 |  |  |
| Sizes  | Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 18.<br>Trays 2-4: Custom Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 139.7 x  |   |                 |  |  |
| Weights  | 16 lb. bond to 140 lb. index / 60 to 256 gsm   |   |                 |  |  |

| Office Finisher LX (Optional)                                    |  |   |  |                          |  |
|--|--|---|--|--------------------------|--|
| Capacity <sup>3</sup>  | Stacking Tray: 2,000 sheets unstaple   | d or 1,000 sheets single stapled or 750         | O sheets dual stapled (8.5 x 11 in. / A4 | )                        |  |
| Sizes  | 7.2 x 8.3 in. to 11.7 x 17 in. / 182 x 210 mm to 297 x 432 mm  |   |  |                          |  |
| Weights  | 16 lb bond to 80 lb cover / 60 to 256 gsm  |   |  |                          |  |
| Multiposition Stapling   | 50 sheets of 24 lb. bond / 90 gsm  |   |  |                          |  |
| Hole Punch (Optional)<br>North America:<br>Europe:               | 2-3 Hole Punch<br>2-4 Hole Punch   | 2-3 Hole Punch                                  |  |                          |  |
| Booklet Maker for Office Finisher L                              | X (Score/Crease, Saddle-stitch Stapl   | e) (Optional)                                   |  |                          |  |
| Capacity <sup>3</sup>  | 40 booklets (2-15 sheets per booklet   | – 20 lb. / 80 gsm or less)                      |  |                          |  |
| Sizes  | Letter – 8.5 x 11 in. / A4 SEF<br>Legal – 8.5 x 14 in. / B4 SEF<br>Ledger – 11 x 17 in. / A3 SEF   |   |  |                          |  |
| Saddle-stitch Stapling   | 2-15 sheets / 8-60 page booklet<br>16 lb. bond to 24 lb. bond / 60 to 90   | gsm   |  |                          |  |
| Score / Crease   | 1-15 sheets / unstapled  |   |  |                          |  |
| Professional Finisher (Optional)                                 |  |   |  |                          |  |
| Capacity <sup>3</sup>  | Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled  Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 or 100 stapled sets of 11 x 17 in. / A3 / SRA3 |   |  |                          |  |
| Sizes  | 4 x 6 in. to 12 x 19 in. / A6 to SRA3 fo<br>7.25 x 10.5 in. to 11 x 17 in. / B5 to A   | 3   |  |                          |  |
| Weights  | 16 lb. bond to 80 lb. cover / 60 to 22   | 0 gsm   |  |                          |  |
| Stapling   | Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported   |   |  |                          |  |
| Hole Punch (Standard)<br>North America:<br>Europe:               | 2-3 Hole Punch<br>2-4 Hole Punch<br>4 Hole Swedish Punch (Optional)  |   |  |                          |  |
| Booklet Maker  | Saddle-stitch 2 to 15 sheets (14 sheets of 90 gsm or less plus 1 sheet of 169 gsm) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 supported   |   |  |                          |  |
| Convenience Stapler (Optional–Inc                                | ludes Work Surface)  |   |  |                          |  |
| Capacity <sup>3</sup>  | 50-sheet stapling<br>5,000 staples<br>Requires a separate outlet   |   |  |                          |  |
| Сору   | WorkCentre 7830  | WorkCentre 7835                                 | WorkCentre 7845                          | WorkCentre 7855          |  |
| First-copy-out Time (Letter/A4-size, from Platen to Centre Tray) | As fast as 8.4 seconds /   | As fast as 8.2 seconds /                        | As fast as 7.5 seconds /                 | As fast as 7.1 seconds / |  |
| (Colour / Black and White)                                       | As fast as 6.7 seconds As fast as 6.8 seconds As fast as 5.5 seconds   |   |  |                          |  |
| Sides (input:output)   | 1-1, 1-2, 2-2, 2-1   |   |  |                          |  |
| Quantity   | 1 to 9,999   |   |  |                          |  |
| Resolution (max.)  | Up to 600 x 600 dpi  |   |  |                          |  |
| Reduction / Enlargement  |  | Variable zoom from 25% to 400% in 1% increments |  |                          |  |
| Concurrency  | Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)  |   |  |                          |  |

| Copy Features            | Annotation and Bates™ stamping (with colour capability and font Authentication for Services (i.e. Colour Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you procollation Covers (Front only, front and back, back only, printed inside and or Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settlings Single Colour Stapling Transparencies | of each section or delete last section as th                                       |   |
|--------------------------|---|--|---|
| Xerox® Copier Assistant® | Xerox® Copier Assistant® Software provides a PC-based alternative PC attached via the USB port, this software supports text-to-speed features. Section 508 compliant. For more information or to down   | h, screen magnification and easy PC keyl   | board access to basic and advanced copy |
| Print                    | WorkCentre 7830 WorkCentre 7835   | WorkCentre 7845  | WorkCentre 7855                         |
| Print Resolution         | Up to 1200 x 2400 dpi   |  |   |
| Print Features           | Application Defaults Banner Sheet Enable / Disable Bi-directional Status Custom Colour Options (Colour By Words) Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, Hig Job Identification (Print ID or Banner, Print ID in margins on first µ Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Bo Overlays Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Saved Job (colour jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Tur    | oage only or all pages) poklet layout / finishing, Fit to new paper  poklet nages) |   |
| Print from USB           | Allows walk-up printing from Type A USB port on front panel<br>Supports direct printing from computer via Type B USB port<br>Supported file formats: PDF, JPEG, TIFF, PS, XPS <sup>4</sup> , PCL<br>Colour jobs can be printed as monochrome  |  |   |
| Operating Systems        | Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64   |  |   |
| Network Protocols        | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Soc<br>NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Ga<br>AppleTalk®: EtherTalk®<br>Microsoft Windows Networking over IP<br>Bonjour®<br>IPv6<br>Secure FTP<br>Most protocols not in use can be disabled   | =  |   |

| Administrative Protocols                              | DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, N  | ITP. DNS. SSDP  |  |  |
|---|--|---|--|--|
| Fonts   | PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts   |   |  |  |
| Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup> | Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.   |   |  |  |
| Xerox® Global Print Driver®                           | A truly universal print driver that lets IT administrators install, upgrade and consistent, easy-to-use interface for end-users, reducing the number of su   | d manage Xerox® and non-Xerox devices from a single driver. It provides a oport calls, and simplifying print services management. |  |  |
| Xerox® Pull Print Driver                              | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.                 |   |  |  |
| Print Solutions                                       |  |   |  |  |
| Xerox® Mobile Print Cloud<br>(Optional)               | Xerox® Mobile Print Cloud addresses the needs of businesses with a mobil without burdening staff, budget or infrastructure. Getting started takes on brand of printer. Accurate printing with true Microsoft® Office® rendering  | ly a few minutes via the cloud. Print from any mobile device to nearly any  |  |  |
| Xerox® Mobile Print Solution<br>(Optional)            | Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment. |   |  |  |
| Unified Address Book for Fax, Inte                    | ernet Fax, Email and Scan to   |   |  |  |
| Features  | Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.   |   |  |  |
| Scan  | WorkCentre 7830 WorkCentre 7835  | WorkCentre 7845 WorkCentre 7855   |  |  |
| Concurrency   | Scan while the system is printing, copying, or while it is transferring scan to concurrent jobs)   | o network or fax jobs (priority is for return of scanned originals and printing   |  |  |
| Input Speed   | Scan at up to 70 ipm colour scanning, up to 70 ipm black and white – 8.5 x 11 in. / A4 LEF   | Scan at up to 133 ipm colour scanning, up to 133 ipm black and white – 8.5 x 11 in. / A4 LEF                                      |  |  |
| Resolution  | 72 x 72 dpi to 600 x 600 dpi<br>Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)   |   |  |  |
| Maximum Scan Area                                     | 11 x 17 in. / A3   |   |  |  |
| Scan Template Management                              | Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options   |   |  |  |
| Network Protocols                                     | sFTP, FTP, SMB, NetWare, HTTP, HTTPS   |   |  |  |
| File Compression                                      | Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression—single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF / PDF/A   |   |  |  |
| Document Management Fields<br>(Meta Data)             | Features only available in Network Scan to File Templates:  • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations  • Customised fields viewed on user interface for variable data input   |   |  |  |
| Scan Features   | Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)   |   |  |  |
| Scan to Email (Standard)                              |  |   |  |  |
| Scan Features   | Email signatures (6 lines each of 128 character max), email message bo     Scan to Email S/MIME Encryption     Email Signing (requires Smart Card option)     Auto send to self  | dy (user configurable), email CentreWare IS confirmation sheet options  |  |  |
| Directory Access                                      | Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domin<br>Downloaded address list (comma-separated file format)<br>Utilises the Unified Address Book   | no)   |  |  |

| Scan to (Standard)                                      | County HCD   |
|---|--|
| Features  | Scan to USB Scan to Network Folder (uses Unified Address Book entries)   |
| Network Scanning – Software Solu                        | tions  |
| Xerox® Scan to PC Desktop®<br>Professional (Optional)   | A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:  • PaperPort Professional image viewing and file management software  - Complete PDF functionality  - Secure PDF workflow of all scanning applications  • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion  • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability   |
| Xerox® ConnectKey® for<br>SharePoint® (Optional)        | Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.   |
| Xerox® ConnectKey® Share to<br>Cloud (Optional)         | ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.  |
| Xerox® ConnectKey® for<br>DocuShare® (optional)         | Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).   |
| Security  |  |
| Features  | Expanded Authentication  Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP  Xerox Secure Access Unified ID System®  Local Authentication (internal database)  Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) /.NET  Secure Data  Digitally signed PDF (when using Smart Card authentication)  Encrypted Scan to Email  Encrypted Password Protected PDF (when using Email and Network Scan Templates only)  Secure Print (up to 10 digit PIN or Network Authentication)  Immediate Image Overwrite  On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk  FIPS 140-2 256 bit Hard Disk Encryption  Expanded Authorisation  SA access based on network credentials  Authorisation per user per service  User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver  Secure Network Access  IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec Identity Services Engine (ISE) integration, Device Security  McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional)  Common Criteria Certification ISO 15408 |
| Xerox Secure Access Unified ID<br>System®<br>(Optional) | Xerox Secure Access Unified ID System integrates your Xerox® multifunction printers with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job.  For more information, go to www.office.xerox.com/software-solutions  |
| Fax   |  |
| Network Server Fax Features  Compatibility              | ITU (CCITT) group 3  |
| Maximum Scan Area                                       | Various Xerox Business Innovation Partner Solutions  11 x 17 in. / A3  |
| Maximum Scan Area Fax Send Features                     | One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)  |
| Fax Print Features                                      | One- or Two-sided Printing, Staple, Secure Print   |
| Transmission Resolution                                 | Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi)<br>Fine: 200 x 200 dpi<br>Standard: 200 x 100 dpi   |
| Internet Fax Features                                   |  |
| Capability  | Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP)  Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients  |
| Directory Access  | Utilises the Unified Address Book  |
| Send / Receive  | Multi-page TIFF, Image only PDF  |
| Resolution  | 72 x 72 dpi to 600 x 600 dpi<br>Bit Depth: 1-bit (black and white)   |
| Network Protocols                                       | SMTP (send), POP3 (receive)  |
| Compliance  | ITU-T T.37 compliant   |

| Walk-up Fax Features (Optional (Cu   | ustomer-installable) – 1 and 2 lines)   |
|--|---|
| Compatibility  | ITU (CCITT) Group 3   |
| Speed / Modems   | One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilising T38 (optional)   |
| Compression / Speed  | MH/G3, MMR/SG3  |
| Resolution   | Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes  |
| Fax Send Features  | LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)  |
| Fax Receive Features   | One- or Two-sided Printing Stapled or Unstapled Receive Print Mode — Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay  |
| Fax Forward  | Forward to Email or SMB Location Fax Forward on Receive Only  |
| Fax Reports  | Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report   |
| Directory Access   | Utilises the Unified Address Book<br>Group fax available  |
| Auto Redial  | Up to 14 attempts (per country requirements)  • 1 to 25 minute intervals  |
| Auto Resend  | Up to 5 attempts  |
| Device Management  |   |
| Management Support   | SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2  |
| Xerox® CentreWαre® Web   | A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:  • Works with any SNMP-managed printer from any manufacturer.  • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.  • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher.  • CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView® |
| Novell NDPS/NEPS   | Server gateway application: centralised management tool.  |
| Xerox® Device Manager  | Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting  • Extensive reporting and discovery of new devices  • Usage collection, chargeback and billing capabilities  |
| Xerox® Device Types for SAP<br>Environment                                   | Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download.  www.office.xerox.com/software-solutions  |
| Xerox® Device Types for SAP<br>R/3 Intelligent Barcode Utility<br>(optional) | Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at <a href="https://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>   |
| Xerox® Barcode Pro PS (optional)   | Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions  |

| CentreWare Internet Services – Inte  | egrated Web Pages Provided by the Device  |
|--------------------------------------|---|
| Device Status                        | Web server embedded in Network Controller:  • Tray status/contents  • Consumables status  • Alerts Remote Control Panel   |
| Job Submission                       | Print ready files: PS, PCL, TIFF, PDF, JPG, XPS <sup>4</sup> , TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)  |
| Device Administration                | Allows simple, remote installation setting of configuration options and management of the device  |
| Browsers                             | Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12  |
| Support                              | Install print / scan drivers and online support available via web page  |
| Languages Supported                  | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese  |
| Remote Print Services                |   |
| Automatic Meter Reading (AMR)        | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.  |
| Automatic Supplies Replacement (ASR) | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).  |
| Accounting                           |   |
| Xerox® Standard Accounting (Stand    | dard)   |
| Tracking                             | Copy, Print, Fax, Scan and Email usage  |
| Accounting                           | Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)   |
| Features                             | <ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>   |
| Accounting Options – Network Acco    | ounting — Third Party Enablement  |
|                                      | <ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul> |
| EFI Fiery Network Server (Optional   |   |
| Processor                            | 2.9 GHz, Intel® Pentium® G850 Dual-Core   |
| Memory (ESS)                         | 1 GB  |
| System Disk                          | 500 GB HDD  |
| Print Languages (PDL)                | PostScript v 3020  Figure Command World Station, canability usin a PC or MAC (systemas to provide) with Outsign Management  |
| Feαtures                             | Fiery Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Colour Tables Expert Colour Settings: Profile, Rendering and Simulation Fiery FreeForm — Variable Data capabilities Booklet Maker 4.0 — booklet wizard to create booklets Print from USB flash drive Paper Catalog Secure Erase EFI PrintMe Fiery® VUE  |
| Connectivity                         | 10Base-TX/100Base-TX/1000Base-T Ethernet  |
| Optional                             | Fiery Options Bundle (Spot-On, Auto Trapping, Hot folders, Virtual Printers)  |

| Supplies                             |  |                      |           |  |
|--------------------------------------|--|----------------------|-----------|--|
| Toner Cartridges (Sold) <sup>5</sup> | Black  | 26,000 pages         | 006R01517 |  |
|                                      | Cyan   | 15,000 pages         | 006R01520 |  |
|                                      | Magenta  | 15,000 pages         | 006R01519 |  |
|                                      | Yellow   | 15,000 pages         | 006R01518 |  |
| Transfer Belt Cleaner                | 1 Assembly   | 160,000 pages        | 001R00613 |  |
| Second Bias Transfer Roll            | 1 Assembly   | 200,000 pages        | 008R13064 |  |
| Staple Cartridges                    | for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton) | 5,000 each cartridge | 008R12964 |  |
|                                      | for Office Finisher LX Booklet Maker (8 cartridges per carton)   | 2,000 each cartridge | 008R12897 |  |
|                                      | for Professional Finisher Booklet Maker (4 cartridges per carton)  | 5,000 each cartridge | 008R12925 |  |
| Staple Refills                       | for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)   | 5,000 each refill    | 008R12941 |  |
| Xerox® Smart Kit®                    |  |                      |           |  |
| Drum Cartridge <sup>6</sup>          | 1 Cartridge per Colour   | 125,000              | 013R00662 |  |
| Waste Toner Container <sup>7</sup>   | 1 Cartridge  | 43,000               | 008R13061 |  |

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit <a href="https://www.xerox.com/about-xerox/recycling">www.xerox.com/about-xerox/recycling</a>.

For more information, visit us at www.xerox.com/office



<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput

<sup>&</sup>lt;sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>&</sup>lt;sup>4</sup> XPS option is required to print XPS files.

<sup>&</sup>lt;sup>5</sup> Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality setpoints.

<sup>6</sup> Average drum yield is based on a run length of 5 pages of 8.5 x 11 in. / A4 LEF pages, with split of 30% colour / 70% black and white pages.

 $<sup>^{7}</sup>$  Waste Toner Container yield will vary depending on type of image, area coverage  $\,\%\,$  and Job run length.